

POINT # 4649

CLASSIFICATION: Section Corner

DESCRIPTION: S.W. CORNER SEC. 07-115-25

PLS MEMO:

Cast Iron Monument (4 inch diameter top) is 1.5 feet west of the centerline of Salem Avenue and 265 feet south of the driveway to house # 12555 Salem Avenue. Top of monument is 0.6 ft below the gravel road surface.

CORNER NORTHING NAD83 (1986):

149476.761

CORNER EASTING NAD83 (1986):

468362.673

REFERENCE NORTHING NAD83 (1986):

REFERENCE EASTING NAD83 (1986):

MONUMENT: 4inch Dia CIM

MEMO:

TIE1 NNE 222.61 ft Nail and disk in the face of a power pole

TIE2 ESE 39.42 ft Nail and disk in the face of a power pole

TIE3 SE 50.87 ft Punch hole in the top end of a culvert

TIE4 SW 55.88 ft Punch hole in the top end of a culvert

Last Date Of Visit: 2004-07-12 00:00:00.0000000

POINT # 4650

CLASSIFICATION: Quarter Corner

DESCRIPTION: W. 1/4 COR. SEC. 07-115-25

PLS MEMO:

Cast Iron Monument (4 inch diameter top) is one foot west of the centerline of Salem Avenue at the intersection with the centerline of 122nd Street. Top of monument is 0.5 ft below the gravel road surface.

CORNER NORTHING NAD83 (1986):

152129.809

CORNER EASTING NAD83 (1986):

468377.912

REFERENCE NORTHING NAD83 (1986):

REFERENCE EASTING NAD83 (1986):

MONUMENT: 4inch Dia CIM

MEMO:

TIE1 NE 53.90 ft Nail and disk in the face of a power pole

TIE2 SE 46.90 ft Nail and disk in the face of a power pole

TIE3 SSE 150.48 ft Nail and disk in the face of a power pole

TIE4

Last Date Of Visit: 2005-05-20 00:00:00.0000000

POINT # 4651

CLASSIFICATION: Section Corner

DESCRIPTION: S.W. CORNER SEC. 06-115-25

PLS MEMO:

Cast Iron Monument (4 inch diameter top) is 3.5 ft west of the intersection centerline of Salem Avenue and 118th Street. Top of monument is 0.5 ft below the gravel road surface.

CORNER NORTHING NAD83 (1986):

154792.94

CORNER EASTING NAD83 (1986):

468392.83

REFERENCE NORTHING NAD83 (1986):

REFERENCE EASTING NAD83 (1986):

MONUMENT: 4inch Dia CIM

MEMO:

May 2005 lower portion of a broken CIM was left in place as an accessory to the corner position.

TIE1 SE 46.95 ft Nail and disk in the face of a power pole

TIE2 SW 40.78 ft Nail and disk in the face of a guy pole

TIE3 NW 46.55 ft Nail and disk in the face of a power pole

TIE4

Last Date Of Visit: 2005-05-19 00:00:00.0000000

POINT # 5071

CLASSIFICATION: Section Corner

DESCRIPTION: S.W. CORNER SEC. 12-115-26

PLS MEMO:

Cast Iron Monument (4 inch diameter top) is in the center line of County Road 134 and 180 feet south of the center line of Preserve Boulevard. Top of monument is flush with the bituminous surface.

CORNER NORTHING NAD83 (1986):

149477.551

CORNER EASTING NAD83 (1986):

463020.531

REFERENCE NORTHING NAD83 (1986):

REFERENCE EASTING NAD83 (1986):

MONUMENT: 4inch Dia CIM

MEMO:

TIE1 NE 106.14 ft SW corner of house # 519 Preserve Blvd

TIE2 SSW 182.96 ft Nail and disk in the face of a power pole

TIE3 WNW 32.54 ft Nail and disk in the face of a power pole

TIE4 NNW 225.91 ft Nail and disk in the face of a power pole

Last Date Of Visit: 2007-08-03 00:00:00.0000000

POINT # 5072

CLASSIFICATION: Quarter Corner

DESCRIPTION: S. 1/4 COR. SEC. 12-115-26

PLS MEMO:

Cast Iron Monument (4 inch diameter top) is approximately 460 feet north of the intersection of Whitetail Path and Barnes Lake Drive. Top of monument is flush with the ground 1 foot southwest of sign post.

CORNER NORTHING NAD83 (1986):

149487.348

CORNER EASTING NAD83 (1986):

465691.711

REFERENCE NORTHING NAD83 (1986):

REFERENCE EASTING NAD83 (1986):

MONUMENT: 4inch Dia CIM

MEMO:

TIE1 NNE 25.64 ft Nail and disk in the face of a 30" Oak tree

TIE2 S 25.15 ft Nail and disk in the face of a 18 " Basswood tree

TIE3 NW 29.34 ft Nail and disk in the face of a 16" Basswood tree

TIE4

Last Date Of Visit: 2006-11-06 00:00:00.0000000

POINT # 5073

CLASSIFICATION: Meander Corner No. 2

DESCRIPTION: M.C.S-Line Sec 12-115-26

PLS MEMO:

Meander Corner No. 2 has not been perpetuated by the county surveyor. It was originally set 7.40 chains east of the quarter corner common to Sections 12 & 13.

CORNER NORTHING NAD83 (1986):

CORNER EASTING NAD83 (1986):

REFERENCE NORTHING NAD83 (1986):

REFERENCE EASTING NAD83 (1986):

MONUMENT: No Monument

MEMO:

TIE1

TIE2

TIE3

TIE4

Last Date Of Visit:

POINT # 5074

CLASSIFICATION: Meander Corner No. 1

DESCRIPTION: M.C.S-Line Sec 12-115-26

PLS MEMO:

Meander Corner No. 1 has not been perpetuated by the county surveyor. It was originally set 2.88 chains west of the northeast corner of Section 13.

CORNER NORTHING NAD83 (1986):

CORNER EASTING NAD83 (1986):

REFERENCE NORTHING NAD83 (1986):

REFERENCE EASTING NAD83 (1986):

MONUMENT: No Monument

MEMO:

TIE1

TIE2

TIE3

TIE4

Last Date Of Visit:

POINT # 5075

CLASSIFICATION: Meander Corner No. 3

DESCRIPTION: M.C. W-LINE SEC. 12-115-26

PLS MEMO:

Cast Iron Monument (4 inch diameter top) is 500 feet northwest of the centerline of Shoreview Lane across from the driveway to house # 544-550 Shoreview Lane. Top of monument is 0.1 ft below ground and one foot south of the sign post.

CORNER NORTHING NAD83 (1986):

151165.923

CORNER EASTING NAD83 (1986):

463035.745

REFERENCE NORTHING NAD83 (1986):

REFERENCE EASTING NAD83 (1986):

MONUMENT: 4inch Dia CIM

MEMO:

There will be future development west of this house and closer to the monument.

TIE1 No local ties available.

TIE2

TIE3

TIE4

Last Date Of Visit: 2006-11-06 00:00:00.0000000

POINT # 5076

CLASSIFICATION: Meander Corner No. 4

DESCRIPTION: M.C. W-LINE SEC. 12-115-26

PLS MEMO:

Cast Iron Monument (4 inch diameter) is 65 feet southeast of the corner of the concrete patio behind house # 100 - 5th Avenue NE. Top of monument is 0.2 ft below ground and one foot east of the sign.

CORNER NORTHING NAD83 (1986):

152443.182

CORNER EASTING NAD83 (1986):

463047.284

REFERENCE NORTHING NAD83 (1986):

REFERENCE EASTING NAD83 (1986):

MONUMENT: 4inch Dia CIM

MEMO:

TIE1 NNE 234.40 ft South corner of house # 104 - 5th Avenue.

TIE2

TIE3

TIE4

Last Date Of Visit: 2006-11-06 00:00:00.0000000

POINT # 5077

CLASSIFICATION: Section Corner

DESCRIPTION: S.W. CORNER SEC. 01-115-26

PLS MEMO:

Cast Iron Monument (4 inch diameter top) is at the approximate centerline intersection of 118th Street and 5th Avenue. Top of monument is 0.9 ft below the gravel road surface.

CORNER NORTHING NAD83 (1986):

154782.704

CORNER EASTING NAD83 (1986):

463068.144

REFERENCE NORTHING NAD83 (1986):

REFERENCE EASTING NAD83 (1986):

MONUMENT: 4inch Dia CIM

MEMO:

TIE1 SSE 125.95 ft Nail and disk in the face of a power pole

TIE2 SSW 139.59 ft NW corner of a block foundation to the garage at house # 403 - 5th Avenue

TIE3 WSW 69.08 ft Nail and disk in the face of a power pole

TIE4 WNW 28.61 ft Punch hole in the top end of a metal culvert

Last Date Of Visit: 2006-06-22 00:00:00.0000000

POINT # 5078

CLASSIFICATION: Quarter Corner

DESCRIPTION: S. 1/4 COR. SEC. 01-115-26

PLS MEMO:

Cast Iron Monument (4 inch diameter top) is 1 foot east of the centerline of Stewart Avenue at the intersection of the centerline of 118th street. Top of monument is 0.7 ft below the gravel road surface.

CORNER NORTHING NAD83 (1986):

154786.794

CORNER EASTING NAD83 (1986):

465712.819

REFERENCE NORTHING NAD83 (1986):

REFERENCE EASTING NAD83 (1986):

MONUMENT: 4inch Dia CIM

MEMO:

TIE1 NE 49.72 ft Punch hole in the top end of a metal culvert

TIE2 SSE 46.12 ft Nail and disk in the face of a post at a phone riser

TIE3 SW 41.72 ft Nail and disk in the face of a power pole

TIE4 WNW 50.88 ft Punch hole in the top end of a metal culvert

Last Date Of Visit: 2006-10-10 00:00:00.0000000